



Ip recorder of 16 channel and 8 mpx resolution with 16 PoE ports

HWN-4216MH-16P

NETWORK FEATURES

PoE ports	16
Number of ports RJ45	1
Velocità RJ45	10 / 100 / 1000 Mbps
Maximum number of users	32
Mobile devices	Android / IOS (Apple)
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Type PoE	802.3at / af
PoE consumption	150W
Software	IVMS
App	Hik-Connect

RECORDING

Maximum recording resolution	8 Mpx
Input bandwidth	160Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Audio compression	G.711A / G.711U / G.722 / G.726
Resolutions	4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Output bandwidth	80Mbps

GENERAL INFORMATION

Serie	Serie 4
Technology	IP
Compatibility	Hikvision HA series cameras

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	8 TB
Type HDD	3,5 SATA"

AUDIO

Audio Inputs	1
Audio Outputs	1

MATERIAL AND DIMENSIONS

Installation	Desktop
Dimensions	385 x 315 x 52 mm
Material	Metal
Net weight	2600 g
Chassis	1U

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
Resolución VGA	1080P
Similar video signals	HDMI and VGA

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	280W

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Maximum humidity	90%

REPRODUCTION AND COPY OF SECURITY

Búsqueda inteligente	Yes
Synchronized playback	16

VIDEO

IP Channels	16
-------------	-----------

INPUTS/OUTPUTS

USB 2.0

2

INTELLIGENT VIDEO SYSTEM

Motion detection

Yes, 2.0 in 4 channels

