



HIKVISION
intrusion

Wired volumetric double technology detector

KX10DTP

DETECTION

Detector type	Wired
Detection distance	10 m
Angle detection	85°
Installation height	1.8 m ~ 2.4 m
Detection method	Infrared and microwave
Pets immunity	Up to 24 kg
Antimasking	Sí
Blue Wave technology (infrared noise improvement)	Sí
Anti-cloaking technology (activation of alarm after infrared detection AND / OR microwave)	Sí
PIR detection advance at ground level (PIR Creep)	Sí
IFT technology	Sí
Detection technology	Volumetric double technology

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V

ESPECIFICACIONES TÉCNICAS

Tamper	Sí
EOL resistors (end of line)	Sí

MATERIAL AND DIMENSIONS

Installation	Wall / ceiling
Dimensions	117 x 69 x 55 mm
Material	ABS plastic

SENSOR

Type of sensor	Pyro-electric
Double PIR sensor	Sí
Sensitivity adjustment	Sí

AMBIENT

Operating temperature	-30 °C ~ 55 °C
Use	Indoor

LENS

Interchangeable lenses	Sí
------------------------	-----------

