



**HIKVISION**  
intrusion

## Wired volumetric double technology detector

**KX15DTAM**

### DETECTION

Detector type	<b>Wired</b>
Installation height	<b>1.8 m ~ 2.4 m</b>
Angle detection	<b>85°</b>
Detection distance	<b>15 m</b>
Detection method	<b>Infrared and microwave</b>
Coverage	<b>15 m / 85°</b>
Antimasking	<b>Yes</b>
Adjustable antimasking	<b>Sí</b>
Blue Wave technology (infrared noise improvement)	<b>Sí</b>
Anti-cloaking technology (activation of alarm after infrared detection AND / OR microwave)	<b>Sí</b>
PIR detection advance at ground level (PIR Creep)	<b>Sí</b>
IFT technology	<b>Sí</b>
Detection technology	<b>Volumetric double technology</b>

### CERTIFICATION

Grade	<b>3</b>
Normative	<b>EN50131</b>
Environmental class	<b>II</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>9V ~ 16V</b>

### MATERIAL AND DIMENSIONS

Dimensions	<b>114 x 67 x 47 mm</b>
Material	<b>Plastic</b>

### SENSOR

Type of sensor	<b>Pyro-electric</b>
Automatic sensitivity	<b>Sí</b>
Curtain sensor	<b>Sí</b>
Microwave	<b>3 microwave frequencies to avoid interference.</b>

### TECHNICAL SPECIFICATIONS

LED indicators	<b>Yes</b>
Tamper	<b>Yes</b>
EOL resistors (end of line)	<b>Sí</b>

### AMBIENT

Operating temperature	<b>-30 °C ~ 70 °C</b>
Use	<b>Indoor</b>

### LENS

Interchangeable lenses	<b>Sí</b>
------------------------	-----------

