

P ▲ R ▲ D O X



wired panel with 5 on-board zones

SP5500

COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
RTC	Sí
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires
Communication with CRA	Yes, through contactID and SIA

ZONES

Maximum number of zones	32
Keyboard areas	1
Wired on-board zones	5
ATZ (Double zones)	Sí, hasta 10 zonas
Maximum number of zones with expanders	24

PROGRAMMABLE OUTPUTS

Board	2
Maximum of PGMs	16
siren	Sí
Telephone line	Sí

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor

CERTIFICATION

Grade	2
Normative	EN50131

VIA RADIO

Extension via radio	Ja, mit dem RTX3-Modul
---------------------	-------------------------------

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	1200mA
Battery support	Sí, 12V 4 ~ 7 Ah

PARTITIONS AND MEMORIES

Partitions	2
User codes	32
Registration events	256
Maximum users	32

ADDITIONAL FEATURES

Calendar	Sí
Software Update	Sí
Mobile app	INSITE GOLD
Call notification	Yes, with IP or PCS module (GPRS)

MATERIAL AND DIMENSIONS

Dimensions	25.5 x 20 x 7.6 mm
Net weight	15 g

GENERAL INFORMATION

Type of Central	Wired
-----------------	--------------

