



HIKVISION
intrusion

Wired volumetric detector

KX15DQ

DETECTION

Detector type	Wired
Installation height	1.8 m ~ 2.4 m
Angle detection	85°
Detection distance	15 m
Detection method	Infrared
Detection speed	0,3 m/s ~ 3 m/s
Detection zones	60
Blue Wave technology (infrared noise improvement)	Si
Detection technology	Volumetric

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V
Relay output type	DC
Relay voltage output	60V
Relay Amperage output	50mA

TECHNICAL SPECIFICATIONS

Compatibility	Wired centrals
Contact resistance	less than 10 ohms
Tamper	Yes
EOL resistors (end of line)	Si

AMBIENT

Operating temperature	-40 °C ~ 80 °C
-----------------------	-----------------------

SENSOR

Type of sensor	Pyro-electric
Sensitivity adjustment	Si
High sensitivity	Si
Low sensitivity	Si
Digital temperature compensation	Yes

MATERIAL AND DIMENSIONS

Installation	Wall / ceiling
Dimensions	117 x 69 x 50 mm
Material	ABS plastic
Net weight	125 g

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

LENS

Lens Type	Ultraviolet light filter
-----------	---------------------------------

