



HIKVISION
intrusion

Wired volumetric detector

KX10DP

DETECTION

Detector type	Wired
Detection distance	10 m
Angle detection	85°
Installation height	1.8 m ~ 2.4 m
Detection method	Infrared
Detection speed	0,3 m/s ~ 3 m/s
Detection zones	52
Pets immunity	Up to 24 kg
Blue Wave technology (infrared noise improvement)	Sí
IFT technology	Sí
Detection technology	Volumetric

ESPECIFICACIONES TÉCNICAS

Compatibility	Wired centrals
Contact resistance	less than 10 ohms
Tamper	Sí
EOL resistors (end of line)	Sí

MATERIAL AND DIMENSIONS

Dimensions	117 x 69 x 50 mm
Material	ABS plastic
Net weight	125 g

AMBIENT

Operating temperature	-40 °C ~ 80 °C
Use	Indoor

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V
Relay output type	DC
Relay voltage output	60V
Relay Amperage output	50mA

SENSOR

Type of sensor	PIR
Sensitivity adjustment	Sí
Low sensitivity	Sí
Digital temperature compensation	Sí

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

