



## ports switch with PoE ports LR1002-1ET



### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-30 °C ~ 65 °C</b> |
| Maximum humidity      | <b>95%</b>            |

### MATERIAL AND DIMENSIONS

|            |                        |
|------------|------------------------|
| Dimensions | <b>79 x 52 x 23 mm</b> |
| Net weight | <b>60 g</b>            |

### CHARACTERISTICS (SWITCH)

|                        |                                               |
|------------------------|-----------------------------------------------|
| Broadband transmission | <b>RG59: 400 m / 100Mbps / 1000m / 10Mbps</b> |
| BNC Port               | <b>1</b>                                      |

### GENERAL INFORMATION

|      |                              |
|------|------------------------------|
| Type | <b>Transmisor EoC Activo</b> |
|------|------------------------------|

### ETHERNET PORTS

|                  |          |
|------------------|----------|
| 10 / 100 Base-TX | <b>1</b> |
|------------------|----------|

### NET STANDARD

|             |            |
|-------------|------------|
| IEEE802,3af | <b>Yes</b> |
| IEEE802,3at | <b>Yes</b> |

### PROTECTION AGAINST RAYS

|                                          |            |
|------------------------------------------|------------|
| Protección sobretensiones línea a tierra | <b>4KV</b> |
| Protección sobretensiones línea a línea  | <b>2KV</b> |

### POWER CONSUMPTION

|                 |           |
|-----------------|-----------|
| Consumption (w) | <b>2W</b> |
|-----------------|-----------|

