



## Seismic detector VV600-PLUS

### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-20 °C ~ 55 °C</b> |
| Degree of protection  | <b>IP30</b>           |
| Maximum humidity      | <b>90%</b>            |

### MATERIAL AND DIMENSIONS

|              |                         |
|--------------|-------------------------|
| Installation | <b>Surface</b>          |
| Dimensions   | <b>81 x 101 x 28 mm</b> |
| Net weight   | <b>380 g</b>            |

### POWER CONSUMPTION

|            |                 |
|------------|-----------------|
| Power mode | <b>DC</b>       |
| Voltage    | <b>9V ~ 15V</b> |

### GENERAL INFORMATION

|            |              |
|------------|--------------|
| Technology | <b>Wired</b> |
|------------|--------------|

### TECHNICAL SPECIFICATIONS

|                   |             |
|-------------------|-------------|
| LED indicators    | <b>Yes</b>  |
| Tamper            | <b>Yes</b>  |
| Low voltage alarm | <b>7.5V</b> |

### DETECTION

|                      |                          |
|----------------------|--------------------------|
| Detection distance   | <b>Radio de 3m ~ 14m</b> |
| Detection technology | <b>Seismic</b>           |

### SENSOR

|                        |                          |
|------------------------|--------------------------|
| Sensitivity adjustment | <b>Interruptores DIP</b> |
|------------------------|--------------------------|

