

HIKVISION
HiWatch Series


Bullet ip camera of 2 megapixels and fix lens

HWI-B121H-M

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
3D-NR	Yes
AGC	Yes
WDR	DWDR
Day / night mode	Automatic / Manual
Bit rate	32Kbps ~ 8Mbps
Compression	H.265 / H.264
Main stream	1080P / 720P (1 ~ 25fps)
Sub stream	D1 / CIF (1 ~ 25fps)

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	4.8W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

DISTANCE DORI

Detect	38 m
Observe	16 m
Recognize	8 m
Identify	4 m

AMBIENT

Operating temperature	-30 °C ~ 50 °C
Degree of protection	IP67
Use	Outdoor

MATERIAL AND DIMENSIONS

Dimensions	186.3 x 70 (Ø) mm
Material	Metal and plastic
Net weight	270 g

AXES

Motion	2-Axis
--------	---------------

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.8'
Minimum lighting	0.01Lux

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.8
Filtro IR	Sí

GENERAL INFORMATION

Serie	HiWatch
Technology	IP
Type of camera	Bullet

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
EXIR	Yes

NETWORK FEATURES

ONVIF	Yes
Web browser	Explorer / Chrome / Firefox / Safari

VIDEO ANALYSIS

Detection type	Basic motion detection (pixel difference)
Motion detection	Yes

ETHERNET PORTS

10 / 100	1
----------	----------

