



Estación exterior modular

VTO4202F-P

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Focal distance	1.95 mm
Horizontal viewing angle	160°
Diagonal angle of view	180°
Night vision	Sí
Video compression	H.264

AMBIENT

Operating temperature	-20 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK07
Use	Outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	100 x 100 x 49.3 mm
Net weight	350 g
Weight with packaging	400 g

GENERAL INFORMATION

Technology	2 Wires / IP
Type	Estación Exterior Modular

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP
IP connection	10M/100Mbps

OPENING

Call elements	Simple buttons
---------------	-----------------------

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	12W
PoE power	Yes

INPUTS/OUTPUTS

RS485	1
Door sensor	1
Exit button	1
Alarm output	1

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Audio compression	G.711A/G.711U/PCM

SYSTEM (RECORDERS)

Processor	SoC processor
Operating system	Embedded LINUX

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
--------	-----------