

UTEPO

Injector poe

UTP7201GE-PSE60



MATERIAL AND DIMENSIONS

Dimensions	160 x 64 x 60 mm
Material	ABS plastic
Net weight	200 g
Weight with packaging	440 g

NET STANDARD

IEEE802,3af	Sí
Hi-PoE	Sí
IEEE802,3at	Sí
PoE+	Yes

POE

Power Pin Assignment	Pair1:1/2(+),3/6(-) Pair2:4/5(-),7/8(+)
Power output	DC54V / 60W
Input port	RJ45
PoE output	RJ45

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V

SPECS AND FEATURES

Type	Injector PoE
------	--------------

PROTECTION AGAINST RAYS

ESD contact to electronic board	8KV
Protección contra sobretensiones	IEC61000-4-2
Protección sobretensiones línea a tierra	PoE : 1KV / Ethernet : 2KV
Protección sobretensiones línea a línea	PoE: 2KV / Ethernet 6KV

ETHERNET PORTS

Transmission distance	Hasta 100 m
10 / 100 / 1000 Base-T	1
POE Ports Speed	10 / 100 / 1000

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Maximum humidity	90%

