



HIKVISION
accessories

Ip of surface / embed video
intercom

DS-KD8003-IME1/S

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	10W
PoE power	Yes
Type PoE	PoE 802.3af

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	98 x 99.8 x 43.9 mm
Material	Stainless steel
Net weight	375 g
Weight with packaging	555 g

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Bidirectional audio	Sí
Audio compression	G.711

AMBIENT

Operating temperature	-40 °C ~ 55 °C
Use	Indoor-outdoor
Maximum humidity	95%

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP
IP connection	10 / 100Mbps autoadaptive

OPENING

Call elements	Simple button
---------------	----------------------

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	180°
Diagonal angle of view	96°
Night vision	Sí
Video compression	H.264

GENERAL INFORMATION

Serie	PVPH
Technology	IP
Number of homes	1

INPUTS/OUTPUTS

Botón de salida	2
Relay NO/NC	2

SYSTEM (RECORDERS)

Processor	Embedded MCU Processor
Operating system	Embedded LINUX

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
--------	-----------

