



HIKVISION
accessories

Ip of surface video intercom DS-KV6113-WPE1(B)

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	10W
Amperage	850mA
PoE power	Yes
Type PoE	PoE 802.3af

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	129°
Diagonal angle of view	75°
Night vision	Si
Video compression	H.264

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	138 x 65 x 27 mm
Net weight	195 g
Weight with packaging	385 g

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP
Memory slot	SD up to 128Gb
IP connection	10 / 100Mbps autoadaptive
Wi-Fi	Si

OPENING

Call elements	Simple button
Proximity reader	MIFARE cards

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Si
--------	----

AMBIENT

Operating temperature	-40 °C ~ 55 °C
Degree of protection	IP65
Use	Indoor-outdoor
Maximum humidity	95%

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Bidirectional audio	Si
Audio compression	G.711

GENERAL INFORMATION

Serie	PVPH
Technology	IP
Number of homes	1

INPUTS/OUTPUTS

Alarm input	4
RS485	1
Relay NO/NC	1

SYSTEM (RECORDERS)

Operating system	Embedded LINUX
------------------	----------------

