



HIKVISION
accessories

Ip of surface / embed video intercom

DS-KV8413-WME1(B)

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	10W
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-40 °C ~ 55 °C
Degree of protection	IP65
Anti vandal	IK08
Use	Indoor-outdoor
Maximum humidity	95%

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP
Memory slot	SD up to 128Gb
IP connection	10M/100Mbps
Wi-Fi	Sí
Tipo de Wi-Fi	2.4 GHz

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Bidirectional audio	Sí
Audio compression	G.711

INPUTS/OUTPUTS

Alarm input	4
RS485	1
Relay NO/NC	2

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
--------	-----------

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	129°
Diagonal angle of view	75°
Night vision	Sí
Video compression	H.264

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	174 x 91 x 29 mm
Net weight	380 g
Weight with packaging	590 g

GENERAL INFORMATION

Serie	PVPH
Technology	IP
Number of homes	4

OPENING

Call elements	4 Botones sencillos
Proximity reader	MIFARE cards

SYSTEM (RECORDERS)

Operating system	Embedded LINUX
------------------	-----------------------

