



RISCO

Wired volumetric double technology detector

RK825DTB000B

DETECTION

| | |
|--|-------------------------------------|
| Detector type | Wired |
| Detection distance | 25 m |
| Angle detection | 83° |
| Installation height | 1.8 m ~ 2 m |
| Detection method | Infrared and microwave |
| Antimasking | Sí |
| Anti-cloaking technology (activation of alarm after infrared detection AND / OR microwave) | Sí |
| Detection technology | Volumetric double technology |

ESPECIFICACIONES TÉCNICAS

| | |
|-----------------------------|--------------------------------|
| LED indicators | Sí |
| LED colors | Verde / Rojo / Amarillo |
| Tamper | Dual |
| EOL resistors (end of line) | Sí |
| Connection type | BUS |

AMBIENT

| | |
|-----------------------|-----------------------|
| Operating temperature | -10 °C ~ 55 °C |
| Use | Indoor |

SENSOR

| | |
|-------------------|--------------------------|
| Type of sensor | PIR and microwave |
| Double PIR sensor | Sí |

POWER CONSUMPTION

| | |
|------------|-----------------|
| Power mode | DC |
| Voltage | 9V ~ 16V |
| Amperage | 40mA |

MATERIAL AND DIMENSIONS

| | |
|-----------------------|-------------------------------|
| Dimensions | 127.6 x 64.2 x 46.6 mm |
| Net weight | 120 g |
| Weight with packaging | 140 g |

CERTIFICATION

| | |
|-----------|----------------|
| Grade | 3 |
| Normative | EN50131 |

