



**HIKVISION**  
accessories

## Reader indoor-outdoor with card mifare 13.56mhz

**DS-K1102AM**

### FEATURES

Integrated controller	<b>No</b>
LED indicator	<b>Si</b>
Sound warning	<b>Si</b>
Tamper	<b>Si</b>
Watchdog design	<b>Si</b>
DIP Switch	<b>Yes</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>
Consumption (w)	<b>2W</b>
Amperage	<b>500mA</b>

### MATERIAL AND DIMENSIONS

Installation	<b>Wall</b>
Dimensions	<b>121 x 86.5 x 14 mm</b>
Net weight	<b>140 g</b>

### SPECS AND FEATURES

Serie	<b>Hika-P</b>
Control type	<b>Reader</b>

### AMBIENT

Operating temperature	<b>-20 °C ~ 65 °C</b>
Degree of protection	<b>IP64</b>
Use	<b>Indoor-outdoor</b>
Maximum humidity	<b>90%</b>

### IDENTIFICATION

Mode	<b>Card</b>
Type of card	<b>MIFARE 13.56MHZ</b>
Maximum reading distance	<b>less than 50 mm</b>

### COMMUNICATION

Mode	<b>Wiegand / RS485</b>
------	------------------------

### FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

Main processor	<b>32 bits</b>
----------------	----------------

