



5 in 1 (hd-cvi, hd-tvi, ahd, analog and ip) recorder of 4 channel and 1 mpx maximum resolution

XVR4104C-I

RECORDING

Maximum recording resolution	1 Mpx
Video compression	H.265+ / H.265 / H.264+ / H.264
Resolution HDCVI recording	1 Megapixel (720P)
Resolution HDTVI recording	1 Megapixel (720p)
Resolution recording AHD	1 Megapixel (720p)
Images per second Main stream	1080N / 720P / 960H / D1 / CIF (1 ~ 25fps)
Images per second Extra stream	CIF (1 ~ 15fps)
Video bit rate	32Kbps ~ 6144Kbps per channel
Recording mode	Manual / Programming (General / Continuous) / MD (Video detection: Motion detection / video loss / manipulation) / alarm / stop
Recording interval	1 ~ 60 min (default: 60 min) / Pre-record: 1 ~ 30 sec / Postrecord: 10 ~ 300 sec
Audio compression	G.711A / G.711U / PCM
Frecuencia muestreo audio	8KHz, 16 bit per channel
Speed audio bits	64Kbps per channel

VIDEO

BNC channels	4
IP Channels	5, replacing the BNC channels
Accepted IP cameras	4 BNC cameras + 1 IP camera
Video formats	HDCVI / TVI / AHD / CVBS / IP
Admitted resolutions HDCVI	1080P / 720P
Admitted resolutions HDTVI	1080P / 720P
Admitted resolutions AHD	1080P / 720P

NETWORK FEATURES

Number of ports RJ45	1
Velocità RJ45	100 Mbps
Maximum number of users	128
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Software	SmartPSS
App	iDMSS / gDMSS

REPRODUCTION AND COPY OF SECURITY

Search mode	Date / Time / Alarm / motion detection / exact search
Playback functions	Play / Pause / Stop / Rewind / Fast play / Slow Play / Next File / Previous File / Next Camera / Previous Camera / Full Screen / Repeat / Shuffle / Backup Selection / Digital Zoom
Backup mode	USB / Network device
Nº canales simultáneos con cámaras IP	1 / 4 / 6
Nº canales simultáneos sin cámaras IP	1 / 4
Tipos de iconos de aviso	Camera title / time / video loss / camera lock / motion detection / recording

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	4W
Amperage	1500mA

AMBIENT

Operating temperature	-10 °C ~ 45 °C
Use	Indoor
Maximum humidity	90%

AUDIO

Audio Inputs	1
--------------	----------

technical datasheet

Cameras CVBS	Yes
--------------	-----

Resolution IP cameras	2 Megapíxeles
-----------------------	---------------

MATERIAL AND DIMENSIONS

Installation	Desktop
--------------	---------

Dimensions	204.6 x 210.9 x 45.6 mm
------------	-------------------------

Net weight	470 g
------------	-------

Weight with packaging	1040 g
-----------------------	--------

Chassis	Smart IU
---------	----------

VIDEO OUTPUT

HDMI Output Number	1
--------------------	---

Number of VGA outputs	1
-----------------------	---

Resolution HDMI	1080P
-----------------	-------

Resolución VGA	1080P
----------------	-------

STORAGE

Number of supported hard drives	1
---------------------------------	---

Maximum hard disk size (Unit)	6 TB
-------------------------------	------

Type HDD	3,5 SATA"
----------	-----------

DETECTION OF VIDEO AND ALARM

Detection functions	Recording / PTZ / Tour / Video Push / Email / FTP / Snapshot / Buzzer and screen tips.
---------------------	--

Type of video detection	Motion Detection / MD Zones : 396 (22 × 18) / Video Loss, Tampering, Diagnosis
-------------------------	--

INPUTS/OUTPUTS

USB 2.0	2
---------	---

Audio Outputs	1
---------------	---

Audio bidirectional (Full-duplex)	Yes
-----------------------------------	-----

GENERAL INFORMATION

Serie	Serie 4
-------	---------

Technology	5 IN 1 (HD-CVI, HD-TVI, AHD, analog and IP)
------------	---

SYSTEM (RECORDERS)

Processor	Embedded Processor
-----------	--------------------

Operating system	Embedded LINUX
------------------	----------------

INTELLIGENT VIDEO SYSTEM

SMD PLUS	Yes, 4 channels (human / vehicle classification) (analog cameras only)
----------	--

