technical datasheet



X

Wireless panel HUB2-DC6V-W

V DDI	I FFAT	IIDEC

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	25
Mobile devices	iOS 9.1 or later / Android 4.1 or later
SIM card number	2
LED indicators	Yes

POWER CONSUMPTION

ode DC	Power mode
4.2V ~ 16V	Voltage
ttery Not	Built in battery
± 16 hours	Battery life
odel 6V DC	Battery model
ent 2200mA @4.2V DC / 500mA @16V DC	Input current
irrent 1500mA	Output current

VIA RADIO

Frequency	868mHz
Transmission	Up to 2000 m (without obstacles)
distance Maximum	Class 4 (2W) / 850/900Mhz , Class 2
power RF	(1W) / 1800/1900MHz

CERTIFICATION

Grade	2
Normative	EN50131

GENERAL INFORMATION

Type of Central Wireless

SABOTAGE

Box tamper Sí

MATERIAL AND DIMENSIONS

MATERIAL AND DIMENSIC	7145
Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	White
COMMUNICATION	
IP	Sí
GPRS	Sí
Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller
AMBIENT	
Operating temperature	5 °C ~ 40 °C
Use	Indoor
ZONES	
Maximum number of room	ns 50
Maximum number of device	ces 100
PARTITIONS AND MEMOR	IES

PROCCESSOR

Maximum users

Operating system OS Malevich

50

