



HIKVISION
HiWatch Series

Minidome ip camera of 2 megapixels and fix lens

HWI-D129H

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Yes
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes
Mirror	On / Off

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	550mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK08
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	97.6 x 121.5 (Ø) mm
------------	----------------------------

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Live view	Up to 6 channels
IP address filter	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.8'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.001Lux

NIGHT VISION

Night vision distance	30 m
Type of night vision	Luz blanca
Number of LEDs	1
Full Color	Yes

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.0
Angle of View	105.2°

GENERAL INFORMATION

Serie	ColorVu
Technology	IP
Type of camera	Minidome

VIDEO ANALYSIS

Detection type	Basic motion detection (pixel difference)
Motion detection	Yes

technical datasheet

Material	Aluminum and plastic
----------	----------------------

Net weight	550 g
------------	-------

Weight with packaging	650 g
-----------------------	-------

DISTANCE DORI

Detect	44 m
--------	------

Observe	18 m
---------	------

Recognize	9 m
-----------	-----

Identify	4 m
----------	-----

AXES

Motion	2-Axis
--------	--------

Video Tamper

Sí

