



Wired curtain volumetric adjustable up to 220 m detector

CH10100001

DETECTION

Detector type	Wired
Installation height	2.5 m ~ 4 m
Angle detection	1.3°
Detection distance	Adjustable up to 220 m
Coverage	220 m x 5.1 m
Detection speed	1 m/s ~ 3 m/s
Antimasking	Sí
PIR detection advance at ground level (PIR Creep)	Sí
Detection technology	Curtain volumetric
360PROtect™	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	10.5V ~ 30V
Amperage	20mA

CERTIFICATION

Grade	3
Normative	EN50131
Environmental class	IV

SENSOR

Type of sensor	PIR
Sensitivity adjustment	Sí

MATERIAL AND DIMENSIONS

Installation	Wall / Post
Dimensions	358 x 188 x 290 mm
Material	Asa
Net weight	1070 g
Weight with packaging	2000 g

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP65
Use	Indoor-outdoor

ESPECIFICACIONES TÉCNICAS

LED indicators	Sí
Tamper	Sí

GENERAL INFORMATION

Serie	ADPRO® PRO E
-------	---------------------

