



Bullet ip camera of 4 megapixels and fix lens

IPC-HFW3441T-AS-P

VIDEO (CAMERAS)

Resolución vídeo	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 8192Kbps
Compression	H.265 / H.264
Main stream	4Mpx (1 ~ 20fps)
Sub stream	704 × 576
Sub stream 2	1080P (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off
E-PTZ	Yes
SSA	Si

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S , G and T
Transmission method	Unicast / Multicast
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	Smart PSS / DSS / DMSS
Mobile devices	Android / IOS (Apple)
Live view	Up to 20 channels
Network disconnection	Yes

VIDEO ANALYSIS

Tipo de detección	Analytical with human/vehicle classification in line/area crossing
Change of scene	Yes
Crossing line	Yes
Intrusion	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Audio detection	Yes
Video Tamper	Sí
Loitering detection	Sí
SMD PLUS	Yes
Detección de parking	Yes

IMAGE

Sensor	CMOS ®
Resolución sensor	2880 x 1620
Sensor Size	1/2.7"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	Color: 0.01Lux / B/W: 0.001Lux
Ratio S / N	More than 56dB

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	550mA
PoE power	Yes
Type PoE	PoE 802.3af

NIGHT VISION

Night vision distance	20 m
Type of night vision	IR

technical datasheet

Conflict of IP addresses	Yes
--------------------------	------------

Cybersecurity	Yes
---------------	------------

LENS

Lens Type	Fix
-----------	------------

Focal distance	2.1 mm
----------------	---------------

Maximum diaphragm opening	F/2.0
---------------------------	--------------

Angle of View	180° (LDC desactivado) / 170° (LDC activado)
---------------	---

Minimum focus distance	600mm
------------------------	--------------

DISTANCE DORI

Detect	52 m
--------	-------------

Observe	21 m
---------	-------------

Recognize	10 m
-----------	-------------

Identify	5 m
----------	------------

AMBIENT

Operating temperature	-40 °C ~ 60 °C
-----------------------	-----------------------

Degree of protection	IP67
----------------------	-------------

Use	Indoor-outdoor
-----	-----------------------

Maximum humidity	95%
------------------	------------

GENERAL INFORMATION

Serie	Wiz Sense
-------	------------------

Technology	IP
------------	-----------

Type of camera	Bullet
----------------	---------------

SYSTEM (CAMERAS)

Ram memory	512 MB
------------	---------------

ROM memory	128 MB
------------	---------------

INPUTS/OUTPUTS (CAMERAS)

Alarm	1 Input / 1 Output
-------	---------------------------

Number of LEDs	2
----------------	----------

IR ON/Off	Automatic / Manual
-----------	---------------------------

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	------------

Audio input	1 Input
-------------	----------------

Audio compression	G.711A / G.711U / G.723 / G.726 / PCM
-------------------	--

Audio output	1
--------------	----------

MATERIAL AND DIMENSIONS

Dimensions	249.3 x 90.7 x 90.4 mm
------------	-------------------------------

Material	Metal
----------	--------------

Net weight	820 g
------------	--------------

Weight with packaging	1090 g
-----------------------	---------------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	--------------------

Storage Systems	NAS / FTP / SFTP / Micro SD
-----------------	------------------------------------

Storage anomaly	Yes
-----------------	------------

AXES

Motion	3-Axis
--------	---------------

