

P ▲ R ▲ D O X

Hybrid panel

MG5050+



COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires
Mobile Network	GPRS / GSM (with PCS module)

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	1200mA
Battery support	Sí, 12V 4 ~ 7 Ah

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor
Maximum humidity	90%

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

PROGRAMMABLE OUTPUTS

Board	4
Maximum of PGMs	16
Telephone line	Sí

VIA RADIO

Frequency	433MHz / 868MHz
-----------	-----------------

ADDITIONAL FEATURES

Calendar	Sí
Software Update	Sí
StayD	Sí
Configuration and remote access	Yes

MATERIAL AND DIMENSIONS

Dimensions	190 x 102 mm
Net weight	170 g
Weight with packaging	220 g

ZONES

Maximum number of zones	32
Wired on-board zones	5
ATZ (Double zones)	Sí

PARTITIONS AND MEMORIES

Partitions	2
User codes	32

GENERAL INFORMATION

Type of Central	Hybrid
-----------------	--------

