



## Wired volumetric detector VXI-DAM-X5

### DETECTION

|                      |                          |
|----------------------|--------------------------|
| Detector type        | <b>Wired</b>             |
| Installation height  | <b>0.8 m ~ 1.2 m</b>     |
| Angle detection      | <b>90°</b>               |
| Detection distance   | <b>12 m</b>              |
| PIR coverage         | <b>2.5 m ~ 12 m</b>      |
| Detection speed      | <b>0,3 m/s ~ 1,5 m/s</b> |
| Detection zones      | <b>16</b>                |
| Antimasking          | <b>Sí</b>                |
| Alarm period         | <b>2.0 ± 1 s</b>         |
| Detection technology | <b>Volumetric</b>        |

### SENSOR

|                        |                          |
|------------------------|--------------------------|
| Type of sensor         | <b>PIR and microwave</b> |
| Sensitivity adjustment | <b>Interruptores DIP</b> |
| Microwave              | <b>10.525 GHz</b>        |
| RF interference        | <b>No alarm 10 V / m</b> |

### MATERIAL AND DIMENSIONS

|                       |                               |
|-----------------------|-------------------------------|
| Dimensions            | <b>81.6 x 199.3 x 70.3 mm</b> |
| Net weight            | <b>380 g</b>                  |
| Weight with packaging | <b>510 g</b>                  |

### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-20 °C ~ 45 °C</b> |
| Degree of protection  | <b>IP55</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>95%</b>            |

### POWER CONSUMPTION

|            |                   |
|------------|-------------------|
| Power mode | <b>DC</b>         |
| Voltage    | <b>9.5V ~ 18V</b> |
| Amperage   | <b>35mA</b>       |

### ESPECIFICACIONES TÉCNICAS

|                |                                               |
|----------------|-----------------------------------------------|
| LED indicators | <b>Yes, Warm up, alarm, masking detection</b> |
| Tamper         | <b>Sí</b>                                     |
| Start time     | <b>60 s</b>                                   |

