

## HIKVISION®



Ip recorder of 32 channel and 32 mpx resolution

DS-7732NXI-I4/S

### RECORDING

|                                                        |                                                                                                                      |
|--------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Maximum recording resolution                           | 32 Mpx                                                                                                               |
| Input bandwidth                                        | 256Mbps                                                                                                              |
| Video compression                                      | H.265+ / H.265 / H.264+ / H.264                                                                                      |
| Channels that support the maximum recording resolution | 32 Mpx y 24 Mpx solo en canal 1 cuando el modo Ultra HD esté activado                                                |
| Audio compression                                      | G.711A / G.711U / G.722 / G.726 / MP2L2                                                                              |
| Resolutions                                            | 32Mpx / 24Mpx / 12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF |
| Output bandwidth                                       | 256Mbps                                                                                                              |

### VIDEO OUTPUT

|                       |              |
|-----------------------|--------------|
| HDMI Output Number    | 2            |
| Number of VGA outputs | 1            |
| Number of BNC outputs | 1            |
| Resolution HDMI       | 4K / 1080P   |
| Resolución VGA        | 1080P        |
| Resolution BNC        | 704 x 576    |
| Similar video signals | HDMI and VGA |

### MATERIAL AND DIMENSIONS

|                       |                   |
|-----------------------|-------------------|
| Installation          | Rack              |
| Dimensions            | 445 x 400 x 75 mm |
| Material              | Metal             |
| Net weight            | 4200 g            |
| Weight with packaging | 6000 g            |
| Chassis               | 1.5U              |

### STORAGE

|                                 |           |
|---------------------------------|-----------|
| Number of supported hard drives | 4         |
| Maximum hard disk size (Unit)   | 10 TB     |
| Type HDD                        | 3,5 SATA" |
| eSata                           | Sí        |

### NETWORK FEATURES

|                         |                                                        |
|-------------------------|--------------------------------------------------------|
| Number of ports RJ45    | 2                                                      |
| Velocità RJ45           | 10 / 100 / 1000 Mbps                                   |
| Maximum number of users | 128                                                    |
| Mobile devices          | Android / IOS (Apple)                                  |
| Remote vision           | Web Browser / Smartphone App and Hik-Connect Software. |
| Software                | IVMS                                                   |
| App                     | Hik-Connect                                            |

### INPUTS/OUTPUTS

|              |    |
|--------------|----|
| Alarm input  | 16 |
| USB 2.0      | 2  |
| USB 3.0      | 1  |
| RS232        | 1  |
| RS485        | 1  |
| Alarm output | 4  |

### POWER CONSUMPTION

|                 |             |
|-----------------|-------------|
| Power mode      | AC          |
| Voltage         | 100V ~ 240V |
| Consumption (w) | 30W         |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 55 °C |
| Use                   | Indoor         |
| Maximum humidity      | 90%            |

### INTELLIGENT VIDEO SYSTEM

|                  |                  |
|------------------|------------------|
| POS              | Yes              |
| VCA              | Sí               |
| Motion detection | Yes, 32 channels |

### REPRODUCTION AND COPY OF SECURITY

|                                      |                                           |
|--------------------------------------|-------------------------------------------|
| Simultaneous cameras in reproduction | 1 / 2 / 4 / 6 / 8 / 9 / 16 / 25 / 32 / 36 |
| Synchronized playback                | 16                                        |

### FACE RECOGNITION

## AUDIO

|                                   |     |
|-----------------------------------|-----|
| Audio Inputs                      | 1   |
| Audio Outputs                     | 1   |
| Audio bidirectional (Full-duplex) | Yes |

## GENERAL INFORMATION

|            |          |
|------------|----------|
| Serie      | Acusense |
| Technology | IP       |

## PERIMETER PROTECTION

|                                |                                                                       |
|--------------------------------|-----------------------------------------------------------------------|
| Channels number with analytics | 4 channels / 12 IVS rules for each channel                            |
| Type of identification         | Human secondary recognition / vehicle for line crossing and intrusion |

## VIDEO

|             |    |
|-------------|----|
| IP Channels | 32 |
|-------------|----|

Number of channels with facial recognition

**1 channel video face recognition / 4 channels facial photo recognition**

Database managment

**Up to 16 databases with 10,000 faces in total / Allows designating name / gender / birth date / nationality / address / Identification information can be added to each face image**

