

**HIKVISION**  
accessories

## ip 7" monitor DS-KH6320-TE1



### POWER CONSUMPTION

|                 |             |
|-----------------|-------------|
| Power mode      | DC          |
| Voltage         | 12V         |
| Consumption (w) | 6W          |
| Amperage        | 1000mA      |
| PoE power       | Yes         |
| Type PoE        | PoE 802.3af |

### SCREEN

|            |            |
|------------|------------|
| Type       | TFT        |
| Size       | 7"         |
| Resolution | 1024 x 600 |
| Touch      | Si         |

### MATERIAL AND DIMENSIONS

|                       |                     |
|-----------------------|---------------------|
| Dimensions            | 200 x 140 x 15.1 mm |
| Net weight            | 330 g               |
| Weight with packaging | 600 g               |

### AUDIO (VIDEO INTERCOM)

|                   |                             |
|-------------------|-----------------------------|
| Sound input       | Multidirectional microphone |
| Sound output      | Built-in speaker            |
| Audio compression | G.711u                      |

### INPUTS/OUTPUTS

|             |   |
|-------------|---|
| Alarm input | 8 |
|-------------|---|

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 55 °C |
| Use                   | Indoor         |
| Maximum humidity      | 90%            |

### SYSTEM (RECORDERS)

|                  |                |
|------------------|----------------|
| Operating system | Embedded LINUX |
| Flash            | 32 MB          |
| RAM              | 128 MB         |

### NETWORK CHARACTERISTICS (INTERCOM MONITORS)

|                  |                       |
|------------------|-----------------------|
| Network protocol | TCP / IP / SIP / RSTP |
| Memory slot      | SD hasta 32Gb         |
| IP connection    | 10M/100Mbps           |

### SPECS AND FEATURES

|            |    |
|------------|----|
| Technology | IP |
|------------|----|

