

P ▲ R ▲ D O X

wired panel with 5 on-board zones

SP5500+



COMMUNICATION

IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	2000mA
Battery support	Si, 12V 4 ~ 7 Ah

MATERIAL AND DIMENSIONS

Dimensions	190 x 90 mm
Net weight	140 g
Weight with packaging	200 g

PARTITIONS AND MEMORIES

Partitions	2
User codes	32
Maximum users	32

ADDITIONAL FEATURES

Calendar	Si
Mobile app	INSITE GOLD
StayD	Si

VIA RADIO

Extension via radio	Ja, mit dem RTX3-Modul
---------------------	------------------------

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

PROGRAMMABLE OUTPUTS

Board	2
Maximum of PGMs	16
Telephone line	Si

ZONES

Maximum number of zones	32
Wired on-board zones	5

GENERAL INFORMATION

Type of Central	Wired
-----------------	-------

