



HIKVISION
HiWatch Series

Minidome ip camera of 4 megapixels and fix lens

HWI-T240HA

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4Mpx (1 ~ 20fps) / 1080P / 720P (1 ~ 25fps)
Sub stream	720P / 640 x 480 / 640 x 360 (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off

IMAGE

Sensor	CMOS ®
Sensor resolution	2560 x 1440
Sensor Size	1/3"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.01Lux
Ratio S / N	Más de 52dB

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.0
Angle of View	99°
Filtro IR	Sí

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels
IP address filter	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	95.2 x 110 (Ø) mm
Material	Metal and plastic
Net weight	290 g
Weight with packaging	510 g

VIDEO ANALYSIS

Detection type	Advanced detection (person/vehicle classification)
Video Tamper	Yes
Classification	Yes
Human / vehicle	

technical datasheet

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
EXIR	Yes
Wavelength	850 nm

DISTANCE DORI

Detect	59 m
Observe	23 m
Recognize	11 m
Identify	5 m

GENERAL INFORMATION

Serie	HiWatch
Technology	IP
Type of camera	Minidome

Motion detection
2.0

Yes (human and vehicle)

AXES

Motion

3-Axis

STORAGE

Storage Systems

FTP

