



A-CCTV

6 ports switch with 4 PoE ports

A-SWITCH-0604POE-60-G-IND

POWER CONSUMPTION

Power mode	DC
Voltage	48V ~ 57V
Standby consumption	5W
Consumption On	120W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	60W
Power supply included	No

ETHERNET PORTS

POE ports	4
Puertos Uplink	1
Fiber port	1 x 1000
10 / 100 / 1000 Base-T	4
POE Ports Speed	10 / 100 / 1000
Uplink ports speed	10/100/1000
Number of Ethernet ports	6

MATERIAL AND DIMENSIONS

Installation	DIN rail / desktop
Dimensions	119 x 100 x 30 mm
Material	Metal
Net weight	360 g
Weight with packaging	440 g

SYSTEM (SWITCH)

MAC address table	2K
-------------------	----

AMBIENT

Operating temperature	-40 °C ~ 80 °C
Degree of protection	IP40
Use	Indoor
Maximum humidity	90%
Lightning protection	6KV

CHARACTERISTICS (SWITCH)

Data rate supported	12 Gbps
Packet redirection speed	8.928 Mpps
Maximum transmission distance	100 m
Buffer Memory	2 Mb
Industrial	Yes

NET STANDARD

IEEE802,3af	Sí
IEEE802,3at	Sí

