



## Double light switch LIGHTCORE-2G



### POWER CONSUMPTION

Voltage	<b>230V</b>
Consumption (w)	<b>0.2W</b>
Connected device power	<b>From 5W to 300W per segment</b>
Current protection	<b>Yes (&gt; 2.6 A)</b>
Temperature protection	<b>Yes (&gt; +60°C)</b>

### AMBIENT

Operating temperature	<b>-10 °C ~ 40 °C</b>
Degree of protection	<b>IP20</b>
Use	<b>Indoor</b>
Maximum humidity	<b>75%</b>

### VIA RADIO

Frequency	<b>868.0 MHz ~ 868.6 MHz</b>
Maximum power RF	<b>Hasta 20 mW</b>
Maximum distance between the device and the hub	<b>1100 m (in open space)</b>

### GENERAL INFORMATION

Type	<b>Double light switch</b>
Compatibility	<b>Hub Plus / Hub 2 (2G / 4G) / Hub 2 Plus / Hub Hybrid (2G / 4G) / ReX / Rex 2</b>

### MATERIAL AND DIMENSIONS

Dimensions	<b>76 x 75 x 29 mm</b>
Net weight	<b>35 g</b>
Weight with packaging	<b>60 h</b>

### SPECIFICATIONS (LIGHT SWITCHES)

Condenser	<b>Included, for devices with consumption &lt; 5W</b>
Electric connection	<b>Only with phase cable</b>
Manageable by scenarios	<b>Yes</b>

