# technical datasheet





# Relay for changeover switch LIGHTCORE-2W

## POWER CONSUMPTION

| 230V           |
|----------------|
| 0.2W           |
| rom 5W to 600W |
| Yes (> 2.6 A)  |
| Yes (> +60°C)  |
|                |

#### **AMBIENT**

| AMDIENI               |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 40 °C |
| Degree of protection  | IP20           |
| Use                   | Indoor         |
| Maximum humidity      | 75%            |

#### VIA RADIO

| Frequency                                       | 868.0 MHz ~               |
|---|---------------------------|
|   | 868.6 MHz                 |
| Maximum power RF                                | Hasta 20 mW               |
| Maximum distance between the device and the hub | 1100 m (in open<br>space) |

# SPECS AND FEATURES

| туре          | Relay for changeover switch               |
|---------------|---|
| Compatibility | Hub Plus / Hub 2 (2G / 4G) / Hub 2 Plus / |
| Compatibilit  | Hub Hybrid (2G /4G) / ReX / Rex 2         |

## MATERIAL AND DIMENSIONS

| Dimensions            | 76 x 75 x 29 mm |
|-----------------------|-----------------|
| Net weight            | 35 g            |
| Weight with packaging | 60 h            |

# SPECIFICATIONS (LIGHT SWITCHES)

| Condenser               | Included, for devices with consumption < 5W |
|-------------------------|---|
| Electric connection     | Only with phase cable                       |
| Manageable by scenarios | Yes   |

