



HIKVISION
accessories

Ip of surface video intercom DS-KV8213-WME1

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	10W
Amperage	700mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-40 °C ~ 55 °C
Degree of protection	IP65
Anti vandal	IK08
Use	Outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	174 x 91 x 29 mm
Net weight	385 g
Weight with packaging	570 g

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	124°
Day / Night	IR
Video compression	H.264

IDENTIFICATION

Type of card	MIFARE 13.56MHz
Number of cards	10000
Number of users	200

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
Led indicator	Sí, 3

INPUTS/OUTPUTS

Alarm input	4
RS485	1
Door sensor	2
Botón de salida	2
Blocking entry	2

SYSTEM (RECORDERS)

Processor	Embedded MCU Processor
Operating system	Embedded LINUX
RAM	256 MB
ROM	32 MB

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP / RSTP
IP connection	10M/100Mbps
Wi-Fi	Sí
Tipo de Wi-Fi	IEEE802.11 b / g / n

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Audio compression	G.711A / G.711U

OPENING

Call elements	2 Botones sencillos
Proximity reader	MIFARE cards

GENERAL INFORMATION

Technology	IP
------------	-----------

