Smoke and heat fire detector

FIREPROTECT2-HS-RB-B

ESPECIFICACIONES TÉCNICAS

Compatibility	**Hub Plus/Hub 2/Hub 2 Plus/Hub Hybrid**
LED indicators	**Sí**
LED colors	**Verde / Rojo / Amarillo**
Tamper	**Sí**
Siren Volume	**85dB to 3 meter**
Temperature activation	**64°C**

AMBIENT

Operating temperature	**0 °C ~ 50 °C**
Degree of protection	**IP20**
Use	**Indoor**
Maximum humidity	**80%**

VIA RADIO

Frequency	**868.0 MHz ~ 868.6 MHz**
Transmission distance	**Up to 1700 m (without obstacles)**
Maximum power RF	**Hasta 20 mW**
Protocol	**Jeweller**

DETECTION

Detector type	**Smoke and heat**

TECHNICAL CHARACTERISTICS

Tipo de notificación	**Acoustics**

MATERIAL AND DIMENSIONS

Dimensions	**124 x 124 x 45 mm**
Net weight	**270 g**
Weight with packaging	**330 g**
Color	**Black**

GENERAL INFORMATION

Technology	**Wireless**
Type	**Fire detector**

POWER CONSUMPTION

Battery model	**2 x CR123A / 3V**
Battery duration	**Up to 7 años**

SENSOR

Type of sensor	**Detección de humo: sensor óptico de doble espectro / Detección de temperatura: termistor**

DETECCIÓN (INCENDIO)

Termovelocimétrico	**10°C / min**