



HIKVISION
accessories

IP video intercom for surface

DS-KV6113-WPE1

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	10W
Amperage	850mA
PoE power	Yes
Type PoE	PoE 802.3af

INPUTS/OUTPUTS

Alarm input	4
RS485	1
Door sensor	1
Botón de salida	1
Relay NO/NC	1

AMBIENT

Operating temperature	-40 °C ~ 55 °C
Degree of protection	IP65
Use	Indoor-outdoor
Maximum humidity	95%

SYSTEM (RECORDERS)

Processor	Embedded MCU Processor
Operating system	Embedded LINUX
RAM	256 MB
ROM	32 MB

AUDIO (VIDEO INTERCOM)

Sound input	Omni-directional microphone
Sound output	Built-in speaker
Audio compression	G.711u

OPENING

Call elements	Simple button
Proximity reader	MIFARE cards

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	131°
Night vision	Sí
Day / Night	IR
Video compression	H.264

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	138 x 65 x 27 mm
Net weight	195 g
Weight with packaging	385 g

IDENTIFICATION

Type of card	MIFARE 13.56MHz
Number of cards	10000
Number of users	2000

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP / RSTP
IP connection	10 / 100Mbps autoadaptive
Wi-Fi	Sí

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
Led indicator	Yes, 2

GENERAL INFORMATION

Technology	IP
------------	-----------

