



Ip recorder of 8 channel and 12 mpx resolution with 8 PoE ports

NVR2108HS-8P-S3

NETWORK FEATURES

PoE ports	8
Number of ports RJ45	1
Velocità RJ45	10 / 100 Mbps
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Remote vision	Web Browser (ActiveX) / Smartphone App / Smart PSS Software
Type PoE	802.3af
PoE consumption	25.5W per port / 72W in total
Software	SmartPSS
App	iDMSS / gDMSS

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	80Mbps
Video compression	H.265 / H.264
Recording mode	Manual / Programmed / Motion Detection / Alarm
Audio compression	G.711A / G.711U / G.726 / PCM
Resolutions	12Mpx / 4K / 5Mpx / 4Mpx / 3Mpx / 1080P / 720P / D1
Output bandwidth	60Mbps

REPRODUCTION AND COPY OF SECURITY

Simultaneous cameras in reproduction	1 / 4 / 8 / 9
Playback functions	Play / Pause / Stop / Fast forward / Fast backward / Rewind / Play by frame / Full screen / Backup (cut/file) / Partially enlarge / Audio on/off
Backup mode	USB
Synchronized playback	8

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1

MATERIAL AND DIMENSIONS

Installation	Desk / Rack
Dimensions	260 x 232.7 x 47.6 mm
Material	Metal
Net weight	890 g
Weight with packaging	2000 g
Chassis	1U

POWER CONSUMPTION

Power mode	DC
Voltage	48V ~ 53V
Consumption (w)	10W
Amperage	1800mA

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	93%

STORAGE

Number of supported hard drives	1
Maximum hard disk size (Unit)	16 TB
Type HDD	3,5 SATA"

VIDEO

IP Channels	8
Resolution IP cameras	12 Megapíxeles

SYSTEM (RECORDERS)

Processor	Industrial grade integrated processor
Operating system	Embedded LINUX

Similar video signals

HDMI and VGA

SPECS AND FEATURES

Serie **LITE**

Technology **IP**

AUDIO

Audio Inputs **1**

Audio Outputs **1**

INPUTS/OUTPUTS

USB 2.0 **2**

