



Minidome ip camera of 5 megapixels and optical zoom lens

IPC-HDBW2541R-ZAS

VIDEO (CAMERAS)

Resolución vídeo	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 8192Kbps
Compression	H.265 / H.264
Main stream	5Mpx (1 ~ 20fps) / 4Mpx (1 ~ 25fps)
Sub stream	704 × 576
Watermark	Yes
Mirror	On / Off
SSA	Si

VIDEO ANALYSIS

Tipo de detección	Analytical with human/vehicle classification in line/area crossing
Change of scene	Yes
Crossing line	Yes
Intrusion	Yes
Motion detection	Yes (4 areas)
Audio detection	Yes
Video Tamper	Si
Classification Human / vehicle	Si
SMD PLUS	Yes

IMAGE

Sensor	CMOS ®
Resolución sensor	2592 x 1944

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S , G and T
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	Smart PSS / DSS / DMSS
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes
Cybersecurity	Yes

DISTANCE DORI

Detect (Open lens)	64 m
Detect (Closed Lens)	222 m
Observe (Open lens)	26 m
Observe (Closed lens)	89 m
Recognize (Open lens)	13 m
Recognize (Closed lens)	44 m
Identify (Open lens)	6 m
Identify (Closed lens)	22 m

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.9W
Amperage	580mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

technical datasheet

Sensor Size	1/2.7'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	Color: 0.005Lux / B/W: 0.0005Lux
Ratio S / N	More than 56dB

LENS

Lens Type	Optical zoom
Focal distance	2.7 mm ~ 13.5 mm
Maximum diaphragm opening	F/1.5
Angle of View	100° ~ 30°
Minimum focus distance	800mm

NIGHT VISION

Night vision distance	40 m
Type of night vision	IR
Number of LEDs	2
IR ON/Off	Automatic / Manual

AUDIO(CAMERAS)

Audio input	1 Input
Audio compression	G.711A / G.711U / G.726 / PCM
Audio output	1

SYSTEM (CAMERAS)

Ram memory	512 MB
ROM memory	128 MB

INPUTS/OUTPUTS (CAMERAS)

Alarm	1 Input / 1 Output
-------	---------------------------

Dimensions	89 x 122 (Ø) mm
Material	Metal
Net weight	490 g
Weight with packaging	670 g

GENERAL INFORMATION

Serie	Serie 2X41
Technology	IP
Type of camera	Minidome

STORAGE

MicroSD-Card	Up to 256Gb
Storage Systems	NAS / FTP / SFTP / Micro SD
Storage anomaly	Yes

AXES

Motion	3-Axis
--------	---------------

