# technical datasheet





# Ip recorder of 8 channel and 32 mpx resolution with 8 PoE ports

NVR5208-8P-EI

NETWORK FE	ATURES	MATERIAL AND DIMEN	NSIONS
PoE ports	8	Installation	Desk / Rack
Number of ports RJ45	1	Dimensions	375 x 329.3 x 53 mm
Velocità RJ45	10 / 100 / 1000 Mbps	Material	Metal
Mobile	Android / IOS (Apple)	Net weight	2520 g
devices	Allaloid / 103 (Apple)	Weight with packaging	<b>3720</b> g
ONVIF	Yes	Chassis	10
Remote vision	Web Browser (ActiveX) / Smartphone App / Smart PSS Software	INPUTS/OUTPUTS	
Type PoE	802.3af/at / Supports ePoE on channels 1 to 8	Alarm input	4
PoE	25.5W per port / 130W in total	USB 2.0	1
consumption Software	SmartPSS	USB 3.0	1
App	iDMSS/gDMSS	RS232	1
АРР	1DN337 9DN33	RS485	1
RECORDING		Alarm output	2
Maximum recording resolution	32 Mpx	INTELLIGENT VIDEO S	YSTEM
Input	70/146	Privacy Mask	Yes
bandwidth Video	384Mbps	SMD PLUS	Yes, 8 channels (human / vehicle classification)
compression	H.265 / H.264	Motion detection	Yes
Recording mode	General / motion detection / smart / alarm / POS	Acupick (intelligent object search)	Yes
Audio compression	G.711A / G.711U / G.726 / PCM	POWER CONSUMPTION	AAN I
	32Mpx / 24Mpx / 16Mpx / 12Mpx / 4K /		
Resolutions	5Mpx / 4Mpx / 1080p / 720p / D1 / CIF / QCIF	Power mode	DC
Output		Voltage	100V ~ 240V
bandwidth	384Mbps	Consumption (w)	10W
VIDEO OUTPUT		REPRODUCTION AND	COPY OF SECURITY
HDMI Output Number 1		Simultaneous cameras reproduction	in 1/4/8/9
Number of VC	GA outputs 1	Backup mode	USB / Network
Resolution HD	OMI 4K		device
Resolución VC	6A <b>4K</b>	Synchronized playback	8
Similar video signals HDMI and VGA		FACE RECOGNITION	
METADATA		Number of faces 12 re	ostros procesados por segundo
Face	Gender / age		

# technical datasheet

Vehícle	Number plate / number plate colour / vehicle model / vehicle logo / vehicle decorations / call sign / seat belts
Human	Style of clothing / color of clothing / hat /
body	bag / umbrella
No	
motorized vehicle	Type / color / helmet / people in vehicle

### **AMBIENT**

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	93%

# STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	16 TB
Type HDD	3,5 SATA"

### **GENERAL INFORMATION**

Serie	Serie 5
Technology	IP

### SYSTEM (RECORDERS)

Processor	Industrial grade integrated
F10CC3301	processor
Operating	Embedded LINUX
system	Lilibeaded Liliox

## PERIMETER PROTECTION

Channels number with	4 channels / 10 IVS rules for
analytics	each channel

Number of	·
channels	
with facial	2 channel video facial recognition
recognition	

Database
managment

Database
managment

Database
managment

Database
managment

Database
managment

Database
managment

databases with 20,000 faces in
total / Allows designating name /
gender / birth date / nationality /
address / Identification information can
be added to each face image

## **AUDIO**

IP Channels

Audio Inputs	1
Audio Outputs	1
VIDEO	

