



5 in 1 (hd-cvi, hd-tvi, ahd, analog and ip) recorder of 4 channel and 1 mpx maximum resolution

HWD-5104MH-G4

RECORDING

Maximum recording resolution	1 Mpx
Video compression	H.265+ / H.265 / H.264+ / H.264
Resolution HDCVI recording	1 Megapixel (720P)
Resolution HDTV recording	1 Megapixel (720p)
Resolution recording AHD	1 Megapixel (720p)
Images per second Main stream	1080P Lite / 720P Lite / WD1 / 4CIF / VGA (1 ~15fps) / CIF (1 ~ 25fps)
Images per second Extra stream	4CIF (15fps) / CIF / QVGA (25fps)
Video bit rate	32 Kbps ~ 4 Mbps
Audio compression	G.711U
Speed audio bits	64Kbps per channel

VIDEO

BNC channels	4
IP Channels	5, replacing the BNC channels
Accepted IP cameras	4 BNC cameras + 1 IP camera
Admitted resolutions HDCVI	1080P / 720P
Admitted resolutions HDTV	1080P / 720P
Admitted resolutions AHD	1080P / 720P
Cameras CVBS	Yes
Resolution IP cameras	2 Megapíxeles

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	1080P
Resolución VGA	1080P
Similar video signals	HDMI and VGA

GENERAL INFORMATION

NETWORK FEATURES

Number of ports RJ45	1
Velocità RJ45	10 / 100 Mbps
Maximum number of users	32
Mobile devices	Android / IOS (Apple)
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Software	IVMS
App	Hik-Connect

MATERIAL AND DIMENSIONS

Installation	Desk / Rack
Dimensions	260 x 222 x 45 mm
Material	Metal
Net weight	800 g
Weight with packaging	1300 g

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	16W
Amperage	1500mA

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

AUDIO

Audio Inputs	1
Audio Outputs	1

REPRODUCTION AND COPY OF SECURITY

Synchronized playback	4
-----------------------	---

INPUTS/OUTPUTS

USB 2.0	2
---------	---

Serie	HiWatch
Technology	5 IN 1 (HD-CVI, HD-TVI, AHD, analog and IP)
Compatibility	Hikvision HA series cameras

STORAGE

Number of supported hard drives	1
Maximum hard disk size (Unit)	4 TB
Type HDD	3,5 SATA"

INTELLIGENT VIDEO SYSTEM

Classification Human / vehicle	Yes
Motion detection	Yes, 2.0 on all analogue channels

