

Milesight



Minidome ip camera of 5 megapixels and fix lens

MS-C5373-PD

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 4 zones
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	16Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
Anti flap	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	2592 x 1944
Sensor Size	1/2.8"
Electronic shutter speed	1s to 1/100,000s
Minimum lighting	0.008 Lux
Ratio S / N	More than 55dB

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S, G, T and Q
Management software	Milesight CMS
IP address filter	Yes
Network disconnection	Yes

DISTANCE DORI

Detect	57 m
Observe	23 m

VIDEO ANALYSIS

Detection type	Analytical with human/vehicle classification in line/area crossing
Crossing line	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Video Tamper	Sí
Loitering detection	Sí
Classification Human / vehicle	Yes

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	90%

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.6
Angle of View	105°

AUDIO(CAMERAS)

Built in microphone	Yes
Audio compression	G.711 / G.722 / G.726 / AAC
Sampling frequency	8 kHz / 16 kHz / 32 kHz / 48 kHz
Bit rate	16 Kbps ~ 256 Kbps

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
Starlight	Yes

MATERIAL AND DIMENSIONS

Dimensions	118.5 x 110.8 x 65 mm
------------	------------------------------

technical datasheet

Recognize	11 m
Identify	6 m

GENERAL INFORMATION

Serie	AI Mini Camera Series
Technology	IP
Type of camera	Minidome

POWER CONSUMPTION

Consumption (w)	6W
PoE power	Yes
Type PoE	PoE 802.3af

STORAGE

MicroSD-Card	Up to 256Gb
Storage Systems	NAS / Micro SD / Recorder
ANR (Redundant Recording in SD)	Yes

Net weight	500 g
Weight with packaging	540 g

AXES

Motion	3-Axis
--------	---------------

