



HIKVISION
accessories

Access control indoor-outdoor with mifare 13.56mhz

DS-K1T805MBWX

INPUTS/OUTPUTS

Alarm input	2
RS485	1
Door sensor	1
Botón de salida	1
Blocking entry	1
Alarm output	1
RJ45	1

IDENTIFICATION

Type of card	MIFARE 13.56MHz
Maximum reading distance	4 cm
Card reading time	menos de 1 s
Number of cards	10000
NUmber of register	100000

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK08
Use	Indoor-outdoor

COMMUNICATION

Wi-Fi	Sí
Bluetooth	Yes

GENERAL INFORMATION

Control type	Access control
--------------	-----------------------

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	12W
Amperage	1000mA

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	177 x 57.7 x 34.6 mm
Net weight	260 g
Weight with packaging	680 g

FEATURES

Integrated controller	Sí
Sound warning	Sí
Tamper	Sí

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

Main processor	Linux
Software	Hik-Connect

