



MOVOK

Minidome ip camera of 5 megapixels and optical zoom lens

VK-IPC-T351-ZAS-I-B

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (140 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 20480Kbps
Compression	H.265 / H.264
Main stream	5Mpx (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Sub stream 2	720P (1 ~ 25fps)
Mirror	On / Off

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	MOVOK (CMS)
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	2880 x 1620
Sensor Size	1/2.7"
Electronic shutter speed	1/3 ~ 1/100000s

DISTANCE DORI

Detect (Open lens)	61 m
Detect (Closed Lens)	200 m
Observe (Open lens)	24 m
Observe (Closed lens)	79 m
Recognize (Open lens)	12 m
Recognize (Closed lens)	40 m
Identify (Open lens)	6 m
Identify (Closed lens)	20 m

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
Funciones IA	Conteo de personas, mapa de calor, detección facial
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Classification Human / vehicle	Yes
SMD	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.2W
Amperage	520mA
PoE power	Yes
Type PoE	PoE 802.3af

NIGHT VISION

Night vision distance	40 m
Type of night vision	IR
IR ON/Off	Automatic / Manual
Starlight	Yes

LENS

Lens Type	Optical zoom
-----------	---------------------

technical datasheet

Minimum lighting	Color: 0.002Lux / B/W: 0.0002Lux
------------------	---

Ratio S / N	More than 56dB
-------------	-----------------------

MATERIAL AND DIMENSIONS

Dimensions	110 x 122 (Ø) mm
------------	-------------------------

Material	Metal
----------	--------------

Net weight	650 g
------------	--------------

Weight with packaging	770 g
-----------------------	--------------

Color	Black
-------	--------------

AMBIENT

Operating temperature	-40 °C ~ 60 °C
-----------------------	-----------------------

Degree of protection	IP67
----------------------	-------------

Use	Indoor-outdoor
-----	-----------------------

Maximum humidity	95%
------------------	------------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	--------------------

Storage Systems	FTP / Micro SD
-----------------	-----------------------

Storage anomaly	Yes
-----------------	------------

SYSTEM (CAMERAS)

Ram memory	128 MB
------------	---------------

ROM memory	256 MB
------------	---------------

Focal distance	2.7 mm ~ 13.5 mm
----------------	-------------------------

Maximum diaphragm opening	F/1.6
---------------------------	--------------

Angle of View	108° ~ 33°
---------------	-------------------

GENERAL INFORMATION

Serie	Serie 3
-------	----------------

Technology	IP
------------	-----------

Type of camera	Minidome
----------------	-----------------

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	------------

Audio compression	G.711A / G.711U / G.726 / G.726ASF
-------------------	---

AXES

Motion	3-Axis
--------	---------------

