

43



MOVOK

Bullet ip camera of 5 megapixels and optical zoom lens

VK-IPC-B351-ZAS-TI-B

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (140 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 20480Kbps
Compression	H.265 / H.264
Main stream	5Mpx (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Sub stream 2	720P (1 ~ 25fps)
Mirror	On / Off

DISTANCE DORI

Detect (Open lens)	67 m
Detect (Closed Lens)	239 m
Observe (Open lens)	27 m
Observe (Closed lens)	95 m
Recognize (Open lens)	13 m
Recognize (Closed lens)	46 m
Identify (Open lens)	7 m
Identify (Closed lens)	23 m

IMAGE

Sensor	CMOS ®
Sensor resolution	2880 x 1620
Sensor Size	1/2.7"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.001Lux

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
AI Functions	People counting, heat map, facial detection
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Heatmap	Yes
People counting	Yes
Classification Human / vehicle	Yes
SMD	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	MOVOK (CMS)
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	550mA
PoE power	Yes
Type PoE	PoE 802.3af

MATERIAL AND DIMENSIONS

Dimensions	244 x 77 x 76 mm
Material	Metal
Net weight	810 g

technical datasheet

Ratio S / N	More than 56dB
-------------	----------------

NIGHT VISION

Night vision distance	50 m
-----------------------	------

Type of night vision	Dual light (IR+Luz blanca)
----------------------	----------------------------

IR ON/Off	Automatic / Manual
-----------	--------------------

Starlight	Yes
-----------	-----

White light	Si
-------------	----

White light distance	50 m
----------------------	------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
-----------------------	----------------

Degree of protection	IP67
----------------------	------

Use	Indoor-outdoor
-----	----------------

Maximum humidity	95%
------------------	-----

GENERAL INFORMATION

Serie	Serie 3
-------	---------

Technology	IP
------------	----

Type of camera	Bullet
----------------	--------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	-------------

Storage Systems	FTP / Micro SD
-----------------	----------------

Storage anomaly	Yes
-----------------	-----

AXES

Motion	3-Axis
--------	--------

Weight with packaging	950 g
-----------------------	-------

Color	Black
-------	-------

LENS

Lens Type	Optical zoom
-----------	--------------

Focal distance	2.7 mm ~ 13.5 mm
----------------	------------------

Maximum diaphragm opening	F/1.0
---------------------------	-------

Angle of View	99° ~ 28°
---------------	-----------

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	-----

Built in speaker	Yes
------------------	-----

Audio compression	G.711A / G.711U / G.726 / G.726ASF
-------------------	------------------------------------

SYSTEM (CAMERAS)

Ram memory	128 MB
------------	--------

ROM memory	256 MB
------------	--------

TIOC

Siren	Yes
-------	-----

Light	White
-------	-------

