

**HIKVISION**  
accessories



## Módulo de seguridad de puerta DS-K2M061

### INPUTS/OUTPUTS

|              |     |
|--------------|-----|
| Alarm input  | 2   |
| RS485        | 1   |
| Door sensor  | Sí  |
| Exit button  | Yes |
| Alarm output | 1   |

### MATERIAL AND DIMENSIONS

|                       |                  |
|-----------------------|------------------|
| Installation          | Wall             |
| Dimensions            | 115 x 48 x 26 mm |
| Net weight            | 130 g            |
| Weight with packaging | 250 g            |

### POWER CONSUMPTION

|            |       |
|------------|-------|
| Power mode | DC    |
| Voltage    | 12V   |
| Amperage   | 500mA |

### GENERAL INFORMATION

|      |                               |
|------|-------------------------------|
| Type | Módulo de seguridad de puerta |
|------|-------------------------------|

### FEATURES

|               |                  |
|---------------|------------------|
| Communication | Wiegand / RS-485 |
| LED indicator | Yes              |
| Tamper        | Sí               |
| DIP Switch    | 4 channels       |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -40 °C ~ 70 °C |
| Use                   | Indoor         |
| Maximum humidity      | 90%            |

