



## 2 wire of surface video intercom DS-KV8103Y-IMPE2

### INPUTS/OUTPUTS

|                 |                |
|-----------------|----------------|
| Alarm input     | 2              |
| Door sensor     | 2              |
| Botón de salida | 2              |
| Blocking entry  | 2              |
| Alarm output    | 1 (12V, 500mA) |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -40 °C ~ 60 °C |
| Degree of protection  | IP65           |
| Use                   | Outdoor        |
| Maximum humidity      | 95%            |

### SYSTEM (RECORDERS)

|                  |                        |
|------------------|------------------------|
| Processor        | Embedded MCU Processor |
| Operating system | Embedded LINUX         |
| RAM              | 256 MB                 |
| ROM              | 32 MB                  |

### AUDIO (VIDEO INTERCOM)

|                   |                             |
|-------------------|-----------------------------|
| Sound input       | Omni-directional microphone |
| Sound output      | Built-in speaker            |
| Audio compression | G.711A / G.711U             |

### CAPACITY

|                                   |     |
|-----------------------------------|-----|
| Events                            | 200 |
| Extensiones interiores vinculadas | 1   |

### OPENING

|               |               |
|---------------|---------------|
| Call elements | Simple button |
|---------------|---------------|

### MATERIAL AND DIMENSIONS

|              |                   |
|--------------|-------------------|
| Installation | Surface           |
| Dimensions   | 169 x 110 x 31 mm |
| Material     | Stainless steel   |
| Net weight   | 545 g             |

### CAMERA

|                          |                |
|--------------------------|----------------|
| Resolution               | 2 Mpx          |
| Horizontal viewing angle | 140°           |
| Night vision             | Yes, up to 3 m |
| Video compression        | H.264          |

### POWER CONSUMPTION

|                 |                            |
|-----------------|----------------------------|
| Power mode      | Powered via indoor station |
| Consumption (w) | 10W                        |

### GENERAL CHARACTERISTICS (VIDEO INTERCOM)

|               |       |
|---------------|-------|
| Tamper        | Sí    |
| Led indicator | Sí, 3 |

### GENERAL INFORMATION

|            |        |
|------------|--------|
| Technology | 2 Wire |
|------------|--------|

### NETWORK CHARACTERISTICS (INTERCOM MONITORS)

|                  |                           |
|------------------|---------------------------|
| Network protocol | TCP / IP / SIP 2.0 / RSTP |
|------------------|---------------------------|

