



28 ports cloud switch with 24 PoE ports

DS-3E1326P-EI

REMOTE MANAGEMENT

P2P	Yes
Software	Hik Pro Connect / IVSM4200
Reset switch	Yes
PoE port reset	Yes
Extended mode activation	Yes, independently per port
Port speed modification	Yes
Actual power consumption	Yes, total and per port
History of peak consumption	Yes (up to 7 days)
Real-time traffic information	Yes, by port
Connected device information	Yes, for Hikvision equipment (IP, model, and SN)
Automatic topology diagram	Yes, for connected Hikvision devices

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	400W
Amperage	6600mA
Standby consumption	30W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	370W

AMBIENT

Operating temperature	0 °C ~ 45 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

NET STANDARD

IEEE802.3af	Yes
IEEE802.3at	Yes

ETHERNET PORTS

POE ports	24
Uplink ports	2
Fiber port	2 x 1000
POE Ports Speed	10 / 100
Uplink ports speed	10/100/1000
Number of Ethernet ports	28
Puertos PoE prioritarios	1 - 8

MATERIAL AND DIMENSIONS

Installation	Rack
Dimensions	440 x 220.8 x 44 mm
Material	Metal
Net weight	2650 g
Weight with packaging	3470 g

CHARACTERISTICS (SWITCH)

Data rate supported	14.8 Gbps
Packet redirection speed	11.01 Mpps
Maximum transmission distance	300 m
Buffer Memory	4 Mb

SYSTEM (SWITCH)

MAC address table	16K
-------------------	------------

