



6 ports cloud switch with 4 PoE ports

DS-3T1306P-SI/HS

REMOTE MANAGEMENT

P2P	Yes
Software	Hik Pro Connect / IVSM4200
Reset switch	Yes
PoE port reset	Yes
Extended mode activation	Yes, independently per port
Port speed modification	Yes
Actual power consumption	Yes, total and per port
History of peak consumption	Yes (up to 7 days)
Real-time traffic information	Yes, by port
Connected device information	Yes, for Hikvision equipment (IP, model, and SN)
Automatic topology diagram	Yes, for connected Hikvision devices

CHARACTERISTICS (SWITCH)

Data rate supported	14 Gbps
Packet redirection speed	10.42 Mpps
VLAN	Yes (max 4094 VLAN)
Maximum transmission distance	300 m
Buffer Memory	1 Mb
PoE Watchdog	Yes
QoS	Yes
Industrial	Yes

MATERIAL AND DIMENSIONS

Installation	DIN rail / desktop
Dimensions	158 x 101.2 x 31.6 mm
Material	Metal
Net weight	390 g
Weight with packaging	960 g

NET STANDARD

IEEE802.3af	Si
IEEE802.3at	Si

POWER CONSUMPTION

Power mode	DC
Voltage	48V
Consumption (w)	65W
Standby consumption	5W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	60W

ETHERNET PORTS

POE ports	4
Puertos Uplink	1
Fiber port	1 x 1000
POE Ports Speed	10 / 100
Uplink ports speed	10/100/1000
Number of Ethernet ports	6

AMBIENT

Operating temperature	-30 °C ~ 65 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

SYSTEM (SWITCH)

MAC address table	2K
-------------------	----

