


HIKVISION
accessories



5 ports cloud switch with 4 PoE ports

DS-3E1505P-EI

REMOTE MANAGEMENT

P2P	Yes
Software	Hik Pro Connect / IVSM4200
Reset switch	Yes
PoE port reset	Yes
Extended mode activation	Yes, independently per port
Port speed modification	Yes
Actual power consumption	Yes, total and per port
History of peak consumption	Yes (up to 7 days)
Real-time traffic information	Yes, by port
Connected device information	Yes, for Hikvision equipment (IP, model, and SN)
Automatic topology diagram	Yes, for connected Hikvision devices

CHARACTERISTICS (SWITCH)

Data rate supported	10 Gbps
Packet redirection speed	7.44 Mpps
VLAN	Yes (max 32 VLAN)
DHCP	Si
Maximum transmission distance	300 m
Buffer Memory	1 Mb
Mirror port	Si
PoE Watchdog	Yes

ETHERNET PORTS

POE ports	4
Uplink ports	1
POE Ports Speed	10 / 100 / 1000
Uplink ports speed	10/100/1000
Number of Ethernet ports	5

NET STANDARD

IEEE802.3af	Yes
IEEE802.3at	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	54V
Consumption (w)	65W
Amperage	1200mA
Standby consumption	≤ 0.9W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	60W

MATERIAL AND DIMENSIONS

Installation	Desk / wall
Dimensions	121.1 x 83.1 x 27.6 mm
Material	Metal
Net weight	220 g
Weight with packaging	750 g

AMBIENT

Operating temperature	0 °C ~ 40 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

SYSTEM (SWITCH)

MAC address table	2K
-------------------	-----------

