


HIKVISION
intrusion

Wired volumetric detector

OCTOPUSDQ

DETECTION

Detector type	Wired
Installation height	2.4 m ~ 4 m
Angle detection	360°
Detection distance	12 m
Detection method	Infrared
Detection speed	0,3 m/s ~ 3 m/s
Blue Wave technology (infrared noise improvement)	Sí
IFT technology	Sí

SENSOR

Type of sensor	Pyroelectric sensor with double element and low noise
Sensitivity adjustment	Sí
High sensitivity	Sí
Half sensitivity	Sí
Low sensitivity	Sí
Automatic sensitivity	Sí
Digital temperature compensation	Yes

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

TECHNICAL SPECIFICATIONS

Tamper	Dual
EOL resistors (end of line)	Sí

MATERIAL AND DIMENSIONS

Installation	Ceiling
Dimensions	33 x 94 (Ø) mm
Material	ABS plastic
Net weight	60 g
Weight with packaging	100 g

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V
Standby consumption	15mA
Consumption On	25mA

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Use	Indoor