



**HIKVISION**  
accessories

## Wi-Fi access point DS-3WF0EC-2NT

### WI-FI

Wi-Fi standard	<b>IEEE802.11 b / g / n</b>
Frequency range	<b>2.4 GHz ~ 2.4835 GHz</b>
Broadband channel	<b>10 / 20 / 40 MHz</b>
Security	<b>WPA2-PSK</b>
Speed	<b>300Mbps</b>
Transmission distance	<b>500m</b>
Angle	<b>65°</b>
Antenna	<b>7dBi</b>
MIMO	<b>2 x 2</b>

### AMBIENT

Operating temperature	<b>-30 °C ~ 70 °C</b>
Degree of protection	<b>IP55</b>
Use	<b>Indoor</b>
Maximum humidity	<b>95%</b>

### INPUTS/OUTPUTS

RJ45	<b>1 x PoE / LAN, 1 x LAN</b>
------	-------------------------------

### ETHERNET PORTS

10 / 100	<b>2</b>
----------	----------

### POWER CONSUMPTION

Consumption (w)	<b>3.7W</b>
PoE power	<b>Yes</b>
Type PoE	<b>12V - 24V PoE</b>
Power supply included	<b>Yes</b>

### MATERIAL AND DIMENSIONS

Dimensions	<b>187.9 x 90.8 x 57.9 mm</b>
Net weight	<b>480 g</b>
Weight with packaging	<b>1020 g</b>

### TECHNICAL CHARACTERISTICS

LED indicator	<b>Si</b>
---------------	-----------

### SOFTWARE

Work Mode	<b>Access Point / Repeater</b>
-----------	--------------------------------