



AJAX

Wireless panel

HUB2-4G-DC6V-W

ADDITIONAL FEATURES

Mobile app	Ajax Security System
SMS notification	Si
Call notification	Si
Notificación Push	Si
Maximum number of connected IP cameras	25
Mobile devices	iOS 9.1 or later / Android 4.1 or later
SIM card number	2
LED indicators	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	4.2V ~ 16V
Built in battery	Not
Battery life	± 16 hours
Battery model	6V DC
Input current	2200mA @4.2V DC / 500mA @16V DC
Output current	1500mA

VIA RADIO

Frequency	868mHz
Transmission distance	Up to 2000 m (without obstacles)
Maximum power RF	Class 4 (2W) / 850/900Mhz , Class 2 (1W) / 1800/1900MHz

ZONES

Maximum number of rooms	50
Maximum number of devices	100

GENERAL INFORMATION

Type of Central	Wireless
-----------------	----------

SABOTAGE

Box tamper	Si
------------	----

COMMUNICATION

Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller
2G/3G	Yes
4G	Yes
Ethernet	Yes

MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	White

AMBIENT

Operating temperature	5 °C ~ 40 °C
Use	Indoor

CERTIFICATION

Grade	2
Normative	EN50131

PARTITIONS AND MEMORIES

Maximum users	50
---------------	----

PROCESSOR

Operating system	OS Malevich
------------------	-------------

