

HIKVISION®

5 in 1 (hd-cvi, hd-tvi, ahd, analog and ip) recorder of 8 channel and 8 mpx maximum resolution

IDS-7208HUHI-M2/X

RECORDING

Maximum recording resolution	8 Mpx
Input bandwidth	256Mbps
Video compression	H.265 / H.264
Resolution HDCVI recording	8 Megapixel (4K)
Resolution HDTVI recording	8 Megapíxeles
Resolution recording AHD	8 Megapíxeles
Images per second Main stream	4K (8fps) / 6Mpx / 5Mpx (12fps) / 4Mpx (15fps) / 3Mpx (18fps) / 1080P / 720P / WD1 / 4CIF / VGA / CIF (25fps)
Video bit rate	32 Kbps ~ 10 Mbps
Audio compression	G.711U
Speed audio bits	64Kbps per channel
Resolutions	4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / 720P / WD1 / 4CIF / VGA / CIF

NETWORK FEATURES

Number of ports RJ45	1
Velocità RJ45	10 / 100 / 1000 Mbps
Maximum number of users	64
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Software	IVMS
App	Hik-Connect

MATERIAL AND DIMENSIONS

Dimensions	385 x 315 x 52 mm
Material	Metal
Net weight	1780 g
Weight with packaging	2820 g

VIDEO

BNC channels	8
Accepted IP cameras	8 BNC cameras + 8 IP cameras
Video formats	HDCVI / TVI / AHD / CVBS / IP
Admitted resolutions HDCVI	8Mpx / 6Mpx / 5Mpx / 4Mpx / 2Mpx / 1Mpx
Admitted resolutions HDTVI	8Mpx / 6Mpx / 5Mpx / 4Mpx / 2Mpx / 1Mpx
Admitted resolutions AHD	5Mpx / 4Mpx / 2Mpx / 1Mpx
Cameras CVBS	Yes

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Number of BNC outputs	1
Resolution HDMI	4K
Resolución VGA	1080P
Resolution BNC	704 x 576
Similar video signals	HDMI and VGA

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	15W
Amperage	3300mA

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	12 TB
Type HDD	3,5 SATA"

SPECS AND FEATURES

Technology	5 IN 1 (HD-CVI, HD-TVI, AHD, analog and IP)
Serie	Serie 7

PERIMETER PROTECTION

Channels number with analytics	8 channels
--------------------------------	-------------------

technical datasheet

Chassis	1U
---------	----

AMBIENT

Operating temperature	-10 °C ~ 55 °C
-----------------------	----------------

Use	Indoor
-----	--------

Maximum humidity	90%
------------------	-----

INPUTS/OUTPUTS

USB 2.0	1
---------	---

USB 3.0	2
---------	---

RS485	1
-------	---

AUDIO

Audio Inputs	1
--------------	---

Audio Outputs	1
---------------	---

REPRODUCTION AND COPY OF SECURITY

Synchronized playback	8
-----------------------	---

FACE RECOGNITION

Number of channels with facial recognition	4 canales reconocimiento facial de vídeo
--	--

Type of identification	Human secondary recognition / vehicle for line crossing and intrusion
------------------------	---

INTELLIGENT VIDEO SYSTEM

Motion detection	Yes, 2.0 on all analogue channels
------------------	-----------------------------------

